



Cleaning Instructions

Although Tarimatec® no maintenance, if that should be cleaned periodically installation to keep it looking good.

It is necessary to clean the space between the slats of organic debris to ensure good water drainage and ventilation.

Tarimatec® requires no special treatment for conservation, but it is possible to paint with lasur or repellent.



If this type of treatment is used, follow the cleaning instructions given by the manufacturer thereof, it is possible that some of the exposed procedure then is not compatible with said protecting and alter its properties.

Tarimatec® is a product installed in the open, and exposed to stains from diverse backgrounds. The most common, which are described below, are cleaned following these recommendations:

Water stains.

Water stains can be produced by splashing pool water, irrigation, download gutters, roofs, etc, or even the same morning dew.

If the installation does not have the correct slope, can produce pools of water that evaporate leaving a visible fence consisting of dissolved substances carries water and even juices that can extract of plant fibers of the stage itself.

These spots are normal for this type of material and not a deficiency Tarimatec® not affecting the quality of the profile.



Cleaning of such spots is very simple. Dip the stage and move the butt or broom clean so that there are no puddles on the platform itself. Allow to dry. If any stain persists, repeat the operation pouring into a bucket with little water, cleaner soap timber. Dip the brush in it and rub the surface to create foam. remove standing water using a broom to avoid the puddle.

To limescale that may persist, use a vinegar cleaner, applied directly on the lama previously moistened with water, then rub and rinse with water, as always, preventing puddle forms.

Spots of soda, wine, coffee.

Soda stains, wine or coffee are removed with a cleaner soap timber. If any These persists, repeat the operation or cleaning diluted bleach solution. Do not leave the bleach acting in the stage long. Rinse with water.

Grease stains, sun cream, oil, etc.

Clean the stain as soon as possible. Remove first with an absorbent paper or cloth, oil, cream or superficial fat. Once you can't withdraw more, apply stain, degreasing cleaner Tarimatec, following instructions:

- Perform cleaning in a sufficiently ventilated place.
- Use latex or vinyl gloves.
- Remove with absorbent paper excess oil, taking care not to spread the stain.
- Dip a cloth or sponge with the cleaner and rub vigorously on the stain on several directions. Repeat 2 times.
- Leave for 1 minute and rinse thoroughly.

· Not to dry, pour into a bucket with little water a dash of dish soap, Fairy type or like. Stir with a clean broom. Soak the brush into the soapy water well bucket and rubbing on the surface treated in various directions until foam.

· Leave for a few minutes and rinse thoroughly. Eliminate possible puddles.

Allow to dry.

This type of stains disappears with the passage of time by the effect of sun and weather. It is recommended not to mount the dais barbecue areas.

Spots of tree resin.

For stains caused by tree resin, clean using a cloth moistened with alcohol Ethyl. Do not apply directly ethyl alcohol leaving it, since it can stain the stage.

Stains Oxido.

For stains, apply stain "Ferrokit". Leave it to dilute the stain and rinse.

Spots decaying organic matter.

Use diluted bleach solution, then scrub with a brush, then rinse thoroughly.

Difficult, unknown or stains.

For stubborn stains of unknown nature, follow different cleaning steps:

- Water
- Cleansing soap
- Diluted bleach (subsequent rinsing with water)
- Bleach concentrated (subsequent rinsing with water)
- Dilute hydrochloric acid (posterior and immediate rinsing with water)



Burnings or surface damage on stage.

For alterations or damage (burns, discoloration by external agents) of the surface of the floors, wipe with a scotch or small grain sandpaper.

On the sanded surface will be a slight change of tone, which can be compared to the rest of the stage with time.

Snow.

To remove the snow, you can use coarse salt and let melt.

Periodic cleaning.

For any stain act as quickly as possible to prevent surface absorption.

Although installation Tarimatec® none outstanding stain, and does not need any maintenance, you should carry out general cleaning every 3 to 6 months, depending on use and area installation, for better appearance and beauty of your installation. To do this, perform cleanup following the following steps:

- Use water jet machine pressure (max. 80 bar) with the jet fan or open and run the water within the meaning of grooving of the stage, avoid circular movements and that leave marks on stage. This will help us remove embedded dirt and dust.



· In a bucket with little water, pour a dash of soap and bleach cleaner, and with a broom clean, rub vigorously in different directions, to create foam. Leave for minutes and rinse with plenty of water and avoid puddles. Allow to dry. Depending on the size of the facility, this cleaning should be done at once or in several areas times.

Tarimatec® surface layer is porous, but the pores are shallow, therefore any stain can remove sanding. If the stain has penetrated the platform, you can sand the surface with

fine sandpaper or wire brush, always in the direction of grooving. This process will produce a slight

whitening the area that will be planed matching the rest of the flooring over time. Except for sudsy cleaner, always perform a clean test in an inconspicuous place of the platform, to observe the results. Strictly follow the cleaning instructions. The use of other cleaning or improper use, are the sole responsibility of the customer.

Tarimatec® is not resistant to acetone, strong acids, silicones and paints.